

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	
<p><b>GENERAL NOTES</b></p> <p>1. EXISTING LIFE SAFETY DEVICES SHALL REMAIN UNLESS NOTED OTHERWISE.</p> <p>2. REFERENCE MECHANICAL, ELECTRICAL, PLUMBING DRAWINGS WHERE APPLICABLE.</p> <p>3. G.C. TO PROVIDE ENGINEERED (STAMPED &amp; SIGNED) DRAWINGS FOR MODIFICATIONS TO THE SPRINKLER AND FIRE ALARM SYSTEM.</p>													<p><b>MATERIAL LEGEND</b></p> <p>--- EXISTING WALL TO REMAIN</p> <p>— EXISTING FIRE RATED WALL TO REMAIN. CONTRACTOR TO VERIFY ALL EXISTING FIRE RATED WALLS &amp; REPAIR AS REQUIRED TO MAINTAIN FIRE RATING</p> <p>— NEW FIRE RATED WALL TO MATCH EXISTING</p> <p>— NEW WALL TO UNDERSIDE OF CEILING</p> <p>— NEW WALL WITH SOUND INSULATION TO UNDERSIDE OF 2ND FLOOR</p> <p>— NEW WALL WITH SOUND INSULATION TO UNDERSIDE OF 2ND FLOOR</p> <p>— NEW WALL TO 6" ABOVE CEILING</p> <p>— AREA NOT IN SCOPE OF WORK</p> <p>ROOM NAME: 201 ROOM INDICATOR</p> <p>— DOOR SWING INDICATOR</p>			<p>REVISION</p> <p>ISSUE FOR PERMIT</p> <p>A/1/16</p>
<p>TRAVEL DISTANCE - XX' (LIMIT 300')</p> <p>COMMON PATH - XX' (LIMIT 100')</p> <p>F.E. BUILDING STANDARD FIRE EXTINGUISHER, MUST COMPLY WITH NFPA 10, TYPE AB, OR C, 10" GC TO SALVAGE EXISTING FIRE EXTINGUISHER FOR RE-USE / PROVIDE NEW</p> <p>*SEE TITLE SHEET FOR EGRESS DOORS AT WAREHOUSE.</p>																

