



TYPE	WEARING SURFACE	BASE	SUB-GRADE
PROPOSED ON-SITE (PAVED AREAS (PARKING LOTS & DRIVE CONNECTIONS))	1-1/2" THICK, TYPE S-III	9" THICK, FOOT APPROVED BASE ROCK, MIN. LBR 100; COMPACTED TO 98% MAXIMUM DRY DENSITY A.A.S.H.T.O. T-180; PRIMED (0.1 GAL PER SY)	12" THICK, COMPACTED TO 98% MAXIMUM DRY DENSITY A.A.S.H.T.O. T-180
PROPOSED DUMPSTER ENCLOSURE SLAB	CONCRETE WITH MINIMUM STRENGTH @ 28 DAYS	N/A	12" THICK, COMPACTED TO 98% MAXIMUM DRY DENSITY A.A.S.H.T.O. T-180
PROPOSED SIDEWALK & BIKE RACK AREA	4" THICK, CLASS 1 CONCRETE WITH MINIMUM STRENGTH @ 28 DAYS	N/A	12" THICK, COMPACTED TO 93% MAXIMUM DRY DENSITY A.A.S.H.T.O. T-180

REQUIRED PAVEMENT & SIDEWALK SPECIFICATIONS

THOMAS F. LUBANOVIC
3333 NORTH FEDERAL HIGHWAY
Professional Engineer No. 56659
John A. Grant, Jr., Inc.
3333 N. Federal Hwy., Ste. 3
Boca Raton, FL 33431

JOHN A. GRANT, JR., INC.
CONSULTING ENGINEERS
3333 NORTH FEDERAL HIGHWAY
BOCA RATON, FLORIDA 33431
PH. NO. 561-3333 FAX NO. 561-395-3315
LICENSED BUSINESS NO. LB 50

1302 WALLACE DRIVE
DELRAY BEACH, FLORIDA 33444

NO.	REVISION	BY	DATE

MADE _____ DATE FEB 2015 F.B. N/A N.T.S. PG _____
CHECKED _____ DATE _____ SCALE _____ OF _____
JOB NO. 35-100-962 SHEET 4 OF 7