

10155 PROVIDE TOILET PARTITIONS AND SCREENS AS INDICATED ON THE DRAWINGS INCLUDING FLOOR-SUPPORTED PARTITIONS AND WALL-HUNG SCREENS. SUBMIT FOR APPROVAL SAMPLES, SHOP DRAWINGS, PRODUCT DATA, COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. PLASTIC LAMINATE-FACED PARTITIONS: PRESSURE-LAMINATED ONE-PIECE FACE SHEETS, 0.062" THICK; SANIWEAL PRODUCTS CO. OR APPROVED EQUAL. COLOR AND FINISH SHALL BE AS SELECTED BY INTERIOR DESIGNER. PROVIDE DOOR HINGES, LATCHES AND COAT HOOK. INSTALL MATERIALS AND SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS. INSTALL MATERIALS AND SYSTEMS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH UNIFORM APPEARANCE. COORDINATE WITH WORK OF OTHER SECTIONS. LIMIT OPENINGS BETWEEN PANELS, DOORS AND PLASTER TO LESS THAN 1/2". ADJUST HARDWARE, CLEAN, AND PROTECT WORK.

10200 PROVIDE LOUVERS AND VENTS INCLUDING ALUMINUM LOUVERS FOR EXTERIOR WALLS, AND SOFFIT AND EAVE VENTS. SUBMIT FOR APPROVAL SHOP DRAWINGS, PRODUCT DATA. COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. PROVIDE FORMED SHEET METAL LOUVERS WITH STATIONARY, HORIZONTAL STORMPROOF BLADES. 16 GAGE GALVANIZED STEEL MINIMUM, INSECT SCREEN; AROLETTE CO. OR APPROVED EQUAL. FINISH LOUVERS IN FLUOROPOLYMER FINISH, 2-COAT, KYMAR 500 OF COLOR AS SELECTED BY ARCHITECT. VENTS SHALL BE EXTRUDED OR BENT ALUMINUM LOUVERS AND FRAMES, WITH PAINTABLE FINISH. COMPLY WITH AMCA STANDARD 500 AND PROVIDE UNITS WITH AMCA CERTIFICATION RATING SEAL. COMPLY WITH SMACNA ARCHITECTURAL SHEET METAL MANUAL EXCEPT AS OTHERWISE INDICATED. TAKE FIELD MEASUREMENTS PRIOR TO FABRICATION. INSTALL UNITS PLUMB AND LEVEL; ISOLATE DISSIMILAR MATERIALS TO PREVENT CORROSION. TOUCH-UP DAMAGED COATINGS. PROVIDE SEPARATE CONTINUOUS SILLS WHERE NEEDED TO PREVENT WATER PENETRATION. MAINTAIN EQUAL BLADE-TO-BLADE AND BLADE-TO-FRAME SPACING FOR UNIFORM APPEARANCE. PROVIDE CONCEALED VERTICAL MULLIONS AND REINFORCEMENT AS NEEDED. PROVIDE ANCHORS, SUPPORTS AND ACCESSORIES AS NEEDED. PROVIDE GASKETS, FLASHINGS AND FILLERS AS NECESSARY TO MAKE INSTALLATION WATER TIGHT.

10425 PROVIDE SPECIALTY BUILDING SIGNAGE AS INDICATED ON THE DRAWINGS AND AS REQUIRED BY CODE FOR THE PHYSICALLY IMPAIRED. SUBMIT FOR APPROVAL SAMPLES, SHOP DRAWINGS, PRODUCT DATA. COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. PANEL SIGNS SHALL BE VOMAR PRODUCTS OR APPROVED EQUAL: FRAMED TYPE, ACRYLIC PLASTIC FABRICATION, ENGRAVED COPY GRAPHICS. METAL LETTERS AND NUMBERS SHALL BE ALUMINUM, FABRICATED UNITS WITH COLOR ANODIZED FINISH AS MANUFACTURED BY LYNN SIGN COMPANY OR APPROVED EQUAL. INSTALL MATERIALS AND SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS. INSTALL MATERIALS AND SYSTEMS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH UNIFORM APPEARANCE. COORDINATE WITH WORK OF OTHER SECTIONS. RESTORE DAMAGED FINISHES. CLEAN AND PROTECT WORK FROM DAMAGE.

10520 FIRE EXTINGUISHER SHALL BE LARSON'S MANUFACTURING CO. DRY CHEMICAL TYPE MODEL MP10 STEEL TANK WITH PRESSURE GAUGE CLASS A,B,C HAVING A 10 LB. CAPACITY. FIRE EXTINGUISHER CABINETS SHALL BE LARSON'S OCCULT SERIES MODEL NO. T-O-A-4016-R FORMED SHEET STEEL PRIMED RECESSED TYPE CABINET SIZED TO ACCOMMODATE FIRE EXTINGUISHER. PROVIDE 5/16" FLAT TRIM, VERTICAL STYLE DOOR, SOLAR GRAY GLASS, AND EXTINGUISHER BRACKET. INSTALLATION SHALL BE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.

10801 TOILET AND BATH ACCESSORIES SHALL BE AS SCHEDULED ON THE PLANS AND SHALL BE BY BOBRICK WASHROOM EQUIPMENT INC., OR ARCHITECT APPROVED EQUAL. ALL PRODUCTS SHALL BE FABRICATED IN STAINLESS STEEL AND SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS TO SATISFY THE REQUIREMENTS OF THE ADA AND APPLICABLE CODES. CONTRACTOR SHALL SUBMIT AN ACCESSORIES SCHEDULE TO ARCHITECT FOR REVIEW PRIOR TO PLACING ORDERS. CONTRACTOR SHALL INSTALL INTERNAL WALL REINFORCEMENT AS REQUIRED TO RECEIVE ACCESSORIES ANCHORAGE.


11450 PROVIDE RESIDENTIAL APPLIANCES FOR WARMING KITCHEN APPLICATION AS INDICATED ON THE DRAWINGS. SUBMIT FOR APPROVAL SHOP DRAWINGS, PRODUCT DATA, WARRANTY, COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. CONTRACTOR TO COORDINATE UTILITY SERVICE AS AVAILABLE AT THE BUILDING. REQUIRED APPLIANCES INCLUDE MICROWAVE OVENS, REFRIGERATOR/FREEZERS, UNDERCOUNTER REFRIGERATORS, HOT WATER DISPENSERS AND FOOD WASTE DISPOSERS. INSTALL MATERIALS AND SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS. INSTALL MATERIALS AND SYSTEMS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH UNIFORM APPEARANCE. COORDINATE WITH WORK OF OTHER SECTIONS. RESTORE DAMAGED FINISHES AND TEST FOR PROPER OPERATION. CLEAN AND PROTECT WORK FROM DAMAGE.

12356 PROVIDE KITCHEN CABINETS AS INDICATED ON THE DRAWINGS. SUBMIT FOR APPROVAL SAMPLES, SHOP DRAWINGS, PRODUCT DATA. COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. CABINETS SHALL BE CONSTRUCTED AND FINISHED AS DESIGNED AND DETAILED BY ARCHITECT AND/OR INTERIOR DESIGNER. LAMINATED CABINET BODIES SHALL BE 3/4 INCH THICK PARTIAL BOARD AND ALL LAMINATED COUNTERTOPS SHALL BE 3/4 INCH THICK PLYWOOD. INSTALL MATERIALS AND SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS. INSTALL MATERIALS AND SYSTEMS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH UNIFORM APPEARANCE. COORDINATE WITH WORK OF OTHER SECTIONS. ANCHOR SECURELY IN PLACE; COORDINATE WITH COUNTERTOP INSTALLATION. ADJUST AND LUBRICATE HARDWARE. RESTORE DAMAGED FINISHES AND TEST FOR PROPER OPERATION. CLEAN AND PROTECT WORK FROM DAMAGE.

12375 PROVIDE PREFABRICATED KITCHEN CABINETS AS INDICATED ON THE DRAWINGS. SUBMIT FOR APPROVAL SAMPLES, SHOP DRAWINGS, PRODUCT DATA, COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. CABINETS SHALL BE CONSTRUCTED AND FINISHED AS DESIGNED AND DETAILED BY INTERIOR DESIGNER. INSTALL MATERIALS AND SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS. INSTALL MATERIALS AND SYSTEMS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH UNIFORM APPEARANCE. COORDINATE WITH WORK OF OTHER SECTIONS. ANCHOR SECURELY IN PLACE; COORDINATE WITH COUNTERTOP INSTALLATION. ADJUST AND LUBRICATE HARDWARE. RESTORE DAMAGED FINISHES AND TEST FOR PROPER OPERATION. CLEAN AND PROTECT WORK FROM DAMAGE.

12500 PROVIDE WINDOW TREATMENT INCLUDING HORIZONTAL BLINDS, VERTICAL BLINDS, DRAPERY TRACK AND/OR SOLAR-CONTROL SHADES AS SELECTED BY INTERIOR DESIGNER. SUBMIT FOR APPROVAL SAMPLES, SHOP DRAWINGS, PRODUCT DATA, MOCK-UPS, WARRANTY, EXTRA STOCK. COMPLY WITH GOVERNING CODES AND REGULATIONS. PROVIDE PRODUCTS OF ACCEPTABLE MANUFACTURERS WHICH HAVE BEEN IN SATISFACTORY USE IN SIMILAR SERVICE FOR THREE YEARS. USE EXPERIENCED INSTALLERS. DELIVER, HANDLE, AND STORE MATERIALS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS. TAKE FIELD MEASUREMENTS PRIOR TO FABRICATION TO ENSURE FIT. INSTALL MATERIALS AND SYSTEMS IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS. INSTALL MATERIALS AND SYSTEMS IN PROPER RELATION WITH ADJACENT CONSTRUCTION AND WITH UNIFORM APPEARANCE. COORDINATE WITH WORK OF OTHER SECTIONS. RESTORE DAMAGED FINISHES AND TEST FOR PROPER OPERATION. CLEAN AND PROTECT WORK FROM DAMAGE.

REVISIONS	BY



Slattery & Associates
ARCHITECTS
PLANNERS

2060 NW BOCA RATON BLVD.
SUITE 2
BOCA RATON, FL 33431
TEL: 561-392-3848
FAX: 561-392-5402
WWW.SLATTERYARCHITECTS.COM

COPYRIGHT © 2014 SLATTERY AND ASSOCIATES, ALL RIGHTS RESERVED.

WOODFIELD HUNT CLUB
CLUBHOUSE RENOVATION
AND EXPANSION
4420 WOODFIELD BLVD.
BOCA RATON, FLORIDA

SLATTERY & ASSOCIATES
FLORIDA REGISTRATION # AM000380

DATE OF SEAL: 7-27-16

SPECIFICATIONS

DRAWN	CR, DR
CHECKED	CR
DATE	7-21-16
SCALE	AS NOTED
JOB NO.	2014-33
SHEET	

A955