


**COLOME & Associates, Inc.**  
**AA 0003439**  
 530 24TH STREET  
 WEST PALM BEACH  
 FLORIDA 33407  
 (561) 833-9147  
 ARCHITECT: ELIZABETH A. & COLOME  
 REG. NUMBER: AR. 0014839




**P.B.C.**  
 R.G. KREUSLER PARK  
 RESTROOM BUILDING  
 AND ENTRY DRIVE  
 MODIFICATIONS

PBC NO 14204  
 2665 SOUTH OCEAN BLVD.

LAKE WORTH  
 FLORIDA

PROJECT NO.  
 201402



SHEET TITLE  
 TYP DETAILS  
 AND  
 SECTIONS

REVISIONS:

DATE  
 11/20/15  
 DRAWN BY:  
 DG  
 CHECKED BY:  
 EP

SHEET  
 NUMBER

S-4

DESIGN LOAD SCHEDULE		(ALL LOADS SHOWN ARE IN POUNDS PER SQ. FT.)	
COMPONENT	AREA	LOAD	TOTAL
METAL TRUSSES	10		
MEP	5		
ROOFING	10		
TOTAL DEAD LOAD		25	
TOTAL LIVE LOAD		20	
TOTAL LOAD		45	






















































BEAM SCHEDULE		REINFORCING		STIRRUPS		
MARK	SIZE BxH (inches)	BOTT	TOP	INT	TIES	SPACING
B-1	8 x 16	3 #5	3 #5	-	#3	@ 6" o.c.
BB-1*	8 x 16	2 #5	2 #5	-	#3	@ 8" o.c.

NOTES:  
 1. TIE-BEAMS INTENDED TO BE CAST ATOP MASONRY WALLS - EXTEND AND HOOK WALL REINFORCING INTO TIE-BEAM.  
 2. \* - INDICATES MASONRY BEAM

FOOTING SCHEDULE		REINFORCING	
MARK	SIZE	BOTT	TOP
F30	3'-0" x 3'-0" x 12"	4 #5 TOP & BOTT. E.W.	
F40	4'-0" x 4'-0" x 16"	5 #5 TOP & BOTT. E.W.	
F45	4'-6" x 4'-6" x 16"	6 #5 TOP & BOTT. E.W.	
F24.12	2'-0" x CONT. x 12"	3 #5 CONT.	
F42.16	3'-6" x CONT. x 16"	4 #5 CONT.	
MF24.12	2'-0" x CONT. x 12"	3 #5 CONT.	
MF24.18	2'-0" x CONT. x 18"	3 #5 CONT. #4 x 2'-0" LONG HOOK BAR @ 36" o.c.	

MASONRY WALL SCHEDULE		REINFORCING	
MARK	THICKNESS	BOTT	TOP
MW-1	8" CMU	#5 @ 40" o.c.	
MW-2	8" CMU	#5 @ 48" o.c.	
MW-3	8" CMU	#5 @ 16" o.c.	

MASONRY WALL NOTES:  
 1. WALL SEGMENTS SHALL BE REINFORCED WITH 9 GA. GALVANIZED LATERAL REINFORCING @ 16" O.C. HORIZ. EXTEND REINFORCING 6" INTO POURED ELEMENTS AND AROUND ENCASED STEEL.  
 2. ADJACENT TO ANY EXTERIOR/INTERIOR WALL OPENING, PLACE (1) MATCHING VERTICAL IN CELL, GROUTED SOLID, FULL HEIGHT.  
 3. ALL MASONRY REINFORCED CELLS SHALL BE FILLED WITH 3000 PSI GROUT MAX.  
 4. AT END, CORNERS, AND INTERSECTION OF WALLS PLACE (1) MATCHING VERTICAL IN CELL GROUTED SOLID, FULL HEIGHT.



**ONMJ**  
 O'Donnell, Naccarato, Mignogna & Jackson  
 STRUCTURAL ENGINEERS  
 821 15TH STREET, SUITE 200  
 WEST PALM BEACH, FLORIDA 33411  
 (561) 835-9994 FAX (561) 835-8255  
 LIC. #0004386  
 JOB # 271.081