

	SPLIT SYSTEM SCHEDULE																																	
	AIR HANDLING UNIT													AIR COOLED CONDENSING UNIT									SYSTEM DATA											
MARK	AREA	MODEL	TOTAL	0/A	ESP	HE	EATER	FA	N EDI	3	EWB	LDB	LWB	WT		UNIT	DIMENSIONS	MARK	MODEL	WT	ELECTRICAL	C	OMPRESS(OR	FAN	UNIT	MAX	CAP	ACITY	EER	IPLV	REF	. LINES	DIMENSIONS
	SERVED		CFM	O/A CFM	-	KW@ 208 V	STEP	— н	P		° F	۴	°F	LBS	MCA F	USE VOLTS-PH-	HZ LXWXH		NO.	LBS	VOLTS-PH-HZ	QTY.	RLA	LRA Q1	Y FLA	MCA	FUSE	TMBH	SMBH			SUCTION	LIQUID] L X W X H
AHU-K-1	SEE PLAN	TWE120E	4000	871	.75	7.5	1	2.	0 78.	3	67.3	54.7	54.2	429	7.8	15.0 208-3-6	0 26X64X55	CU-K-1	TTA120E3	424	208-3-60	2	16.0 (EACH.)	110.0 (EACH.)	1 5.0	41.0	45	124.0	97.02	11.2	12.2	1-1/8	1/2	52X40X40
9	SPLIT S	YSTEM NOT	<u> </u>																															
2. P	ROVIDE FACT	DESIGN CONDITIONS: TORY INSTALLED ST BLE WALL CONSTRU	AINLESS	STEEL			EACH-FL).	10.	PROVIDE PROVIDE NON POV	CONDEN	Y INSTALL SING UNIT	ED CRANI S WITH S	CASE HEATE NGLE POINT F	ER. POWER, DIS	CONNECT	SWITCH,	16. CONTE	RACTOR TO	VERIFY AHU H	AND FOR	TH 3/4" FIRE RE	ND ACC	ess priof	r to ordef										
4. P 5. P	ROVIDE CONI ROVIDE AHU,	DENSATE OVERFLOW /CU WITH DUAL RI	SWITCI FRIGER	H. RATION (CIRCUI ⁻	TS.	'DV 7	11. 12.	PROVIDE PROVIDE	FACTOR' CONDEN	SING UNIT	ΓW/ COR	R TUBE ALUM	ECTION ON	CONDENS	ER COIL.					S IN COMPLIANCE E THE BASIS OF			ISTANCE AS	PER FBC.	•								
7. Pf	ROVIDE 1"SPF	R RACK FOR AHU. RING ISOLATION FOR I—IN DISCONNECT W	AHU.				.KV /.		RECOMME	NDATION	IS.		AS MANUFAC INER IN REFR							<u> </u>			1											

MARK	SELECTION BA	SED ON		AREA SERVED	CFM	ESP	RPM		MOTOR	DATA	DRIVE	SONES	UNIT	ACCESSORIES
WATER	MAKE	TYPE	MODEL NO.			IN WG		HP	RPM	VOLTS-PH-HZ		OR NC	WEIGHT	REMARKS
EF-J-1	GREENHECK	CABINET CASSETTE FAN	SP-110-VG	JANITOR'S CLOSET	100	0.30	940	8 W		120-1-60	DIRECT	_	24	
KSF-1	CAPTIVEAIRE	DOWNBLAST CENTRIFUGAL FAN	#A2-G15	KITCHEN HOOD-MAKEUP AIR	3984	0.750	669	2.00	1725	208-1-60	BELT	12	370	4,6
KEF-1	CAPTIVEAIRE	DOWNBLAST CENTRIFUGAL FAN	NCA16FA	KITCHEN HOOD-EXHAUST	2460	1.20	1090	1.50	1725	208-1-60	BELT	12.9	157	4,6
KEF-2	CAPTIVEAIRE	DOWNBLAST CENTRIFUGAL FAN	NCA16FA	KITCHEN HOOD-EXHAUST	2520	1.20	1094	1.50	1725	208-1-60	BELT	13	157	4,6
CHEF-1	GREENHECK	ÚÞBĽASŤ CENTRIFUGAL FAN	CUE-101HP-VG	DISHWASHER-EXHAUST	300	1.20	1825	0.50	2500	208-1-60	DIRECT	9.6	61	4,8
3. ALL OUTDOO OR NOT EX FROM THE I 4. COORDINATE ANY EQUIPM 5. SEE GENERA OTHER FIELD 6. PROVIDE FAC 7. ALL ROOF M	CEED A NOISE LEVEQUIPMENT IN ALL TWITH ELECTRICAL MENT. AL, AIR CONDITIONI O SUPPLIED ITEMS. CTORY FAN MOUNT	ALL COMPLY WITH LOCAL ZO EL OF 55DB AS MEASURED DIRECTIONS. CONTRACTOR BEFORE BIDD NG, DUCTWORK, AND COORD ING SUPPORTS-LEGS, CURB ED TO HAVE MIAMI DADE CO	ONING NOISE ORDINANCE RADIALLY 15 FT. ING OR ORDERING INATION NOTES FOR IS, HANGING CLIPS, ETC.	3. PROVIDE WITH GREASE TRAP KIT. 4. PROVIDE WITH FACTORY CURB KI 5. FAN BLADES MUST BE FACTORY 6. MIAMI-DADE NOA# 14-0722.16 E 7. CORROSION RESISTANT FAN MOU 8. MIAMI-DADE NOA# 16-0209.05 E	T. ADJSUTE IXP. DAT INT FAN IXP. DAT	E: MARCI OUT OF IE: SEPTE	H 4, 2019. THE AIR S MBER 23,	TREAM	s represen	ITATIVE.				





PROJECT: KITCHEN RENOVATION TO NORTH HOMELESS ASSISTANCE CENTER BROWARD COUNTY

SHEET TITLE:

MECHANICAL INDEX,

SYMBOL LEGEND AND NOTES

Output

SYMBOL LEGEND AND NOTES